


APPENDIX 5
PHASE I - VARIANCE DECISION AMENDMENT
#2 DATED JULY 22, 2005



**STATE OF NEW YORK
DEPARTMENT OF LABOR
www.labor.state.ny.us**

DATE: 7/22/05

DELIVER TO:

Name: ARNEL JAVAL/EDGERTS (TRC) 212-221-7840
 PATEVANGELISTA (EPA) 212-637-4445
 KRISH RAOHAKRISHNAN (DEP) 718-595-3744
 ROBERT IULO (NYC DDO) 212-566-3848
Office: RICHARD FELM (DEC) 718-482-4874
 GIL GILLEN (OSHA) 212-337-2371

Location:

Floor:

Room:

Phone No:

Fax No:

FROM:

Name: CHRISTOPHER ALONZE

Office: Engineering Services

Location: Bldg 12, Room 154
 State Campus, Albany, NY 12240

Phone No: 518-457-1536

Fax No: 518-457-1301

COMMENTS:

VARIANCE DECISION AMENDMENT #12
 RELATING TO: VALVE DUCTS & TRACEWAYS CLEANING/INSPECTION PROCEDURES
 &
 PILOT PROGRAM FOR REMOVAL OF COLUMN COVERS

NUMBER OF PAGES BEING TRANSMITTED:

(Including cover sheet)

This communication is intended only for the use of the named addresses and may contain information which is privileged, confidential and/or exempt from disclosure under applicable law. If the reader of this communication is not the intended recipient, you are hereby notified that any dissemination, distribution, or copying of this communication is strictly prohibited. If you receive this communication in error, please notify me immediately by telephone to arrange the immediate return of the communication.

STATE OF NEW YORK
DEPARTMENT OF LABOR
STATE OFFICE BUILDING CAMPUS
ALBANY, NEW YORK 12240-0100

Variance Decision Amendment

Premises: Vacant High Rise Office Building
130 Liberty Street
New York, New York

**Amendment: Revised Procedures &
Conditions**

File No. 05-0427

DECISION
AMENDMENT
#2

ICR 56

The site-specific variance decision file no. 05-0427, dated May 11, 2005, is hereby amended as follows:

AMENDMENT CONDITIONS

1. This amendment is based upon the amendment/reopening request that was submitted by TRC, dated June 10, 2005, the revised pilot program work plan dated June 24, 2005 and the additional information for walker ducts & raceway cleaning protocols dated July 7, 2005, totaling twenty-four pages. The amendment/reopening request for revised procedures and conditions to address several outstanding issues is approved, as modified by this decision amendment. A copy of the marked-up request is attached to this decision amendment.
2. Prior to commencement of "Pre-demolition Cleaning and Abatement" asbestos project work including scaffold installation and other preparatory work, revised plans for the entire deconstruction project shall be submitted to all pertinent federal, state and local regulatory agencies, and all necessary approvals obtained.
3. All proposed air monitoring for contaminants other than asbestos must be submitted to the appropriate regulatory agency for their review and approval prior to the commencement of any asbestos project work, including scaffolding installation and other preparatory work. The

Department will not grant or deny approval for any proposed non-asbestos contaminant air monitoring procedures.

4. The original variance decision condition #42 is now modified to include the provisions and conditions of this variance decision amendment.

Cleaning, Visual Inspection and Clearance of Walker Ducts and Raceways

5. Both the project monitor and supervisor shall observe all visual (including videotaped) duct inspections. The on-site project monitor is responsible for determining if additional cleaning is necessary within the ducts and raceways prior to successful completion of the visual inspection for any portion of a specific work area.
6. The proposed Walker Duct and Raceway cleaning procedures/protocol is conditionally accepted by the Department, dependent upon the effectiveness demonstrated for the initial interior work area. The local district of the Department's Asbestos Control Bureau shall be contacted, and an inspection scheduled to demonstrate the effectiveness of these cleaning procedures/protocols. The Department reserves the right to issue modifications to the cleaning procedures/protocol based upon observations and visual inspection results for the initial interior work area.

Pilot Program For Removal of Aluminum Column Covers & Fascia With Non-friable ACM Caulking

Exterior Negative Pressure Tent Fireproofing Removals

7. All conditions of the previous variance decision amendment apply to the fireproofing removals completed at the exterior of the building within negative pressure tent enclosures.
8. The results of the pilot program shall be submitted to all pertinent regulatory agencies for their review and approval. Until approval is obtained from all pertinent regulatory agencies, any disturbance to ACM caulking shall be completed within negative pressure tent enclosures as per the conditions of the variance decision and current reopenings/amendments.

Waste Decontamination System Enclosure

9. When a remote personal decontamination system enclosure is allowed and utilized for a regulated abatement work area, the following requirements shall apply:
 - a. Minor Size Regulated Abatement Work Area. No specific waste decontamination system enclosure is required for minor size regulated abatement work areas. The waste generated shall be

immediately bagged/containerized within the regulated abatement work area.

- b. Small & Large Size Regulated Abatement Work Areas.
- i. **Washroom.** An additional chamber shall be constructed within the regulated abatement work area, attached to the existing airlock used to access the work area. The washroom/airlock combination shall be utilized as the contiguous waste decontamination enclosure for waste bagging/containerization and waste transfer activities. The washroom shall be constructed and supplied with equipment/materials consistent with waste decontamination system enclosure washroom requirements for contiguous personal and waste decontamination system enclosures.
 - ii. **Removal.** The washroom chamber shall be removed only after satisfactory clearance air sampling results have been achieved or the asbestos project is complete.

Exterior Regulated Abatement Work Area Air Monitoring Requirements.

10. For exterior regulated abatement work areas, including but not limited to façade cleaning, netting removal, hoist/scaffold tie-ins and tent enclosure work, air monitoring requirements of ICR 56-17 apply, unless modified by the original variance decision (i.e. tent enclosures). In addition, all proposed air monitoring for contaminants other than asbestos must be submitted to the appropriate regulatory agency for their review and approval, prior to the commencement of any phase I work, including scaffolding installation. The Department will not grant or deny approval for any proposed non-asbestos contaminant air monitoring procedures.
11. All other provisions of the variance decision remain in force.

Date: July 22, 2005



Christopher E. Alonge, P.E.
Senior Safety and Health Engineer



Customer-Focused Solutions

05 0427

June 10, 2005

File No. 05-427

Christopher Alonge, P.E.
 NYS Department of Labor
 Engineering Services Unit
 State Campus Bldg. 12, Room 154
 Albany, NY 12240

RECEIVED

JUN 13 2005

Subject: Variance Reopening (2) for Walker Duct and Raceway Cleaning Project
 Regarding File No. 05-0427; 130 Liberty Street, New York, NY

ENGINEER
 STATE OF NEW YORK
 ALBANY, NY

Dear Mr. Alonge,

We respectfully submit for consideration the additional information regarding the referenced File No. for this project. Please note the following protocol replaces the procedure submitted previously with the original submission:

Cleaning, Visual Inspection and Clearance of Walker Ducts and Raceways

It is the intent of this work to clean and remove all dirt, dust and debris from the raceway and walker ducts in the floor cabling system. If after video inspection and/or testing, it is determined that areas have not been thoroughly cleaned, those areas shall be re-cleaned by the contractor. Third party inspections will be conducted by the Owner's representative. This work will be done during the Asbestos Abatement Project under negative pressure.

1. Work to be performed will include the following:

- Removal of raceway/duct access plates, as necessary.
- Removal of all wires and cables from the ducts/raceways.
- Isolation of ducts, as required, to prevent cross contamination.
- Cleaning of all East to West Raceways (approx 2" x 6") on all floors.
- Cleaning of all Walker Ducts (1" x 4") on all floors.
- Cleaning of all terminal drops to floor ducts which are part of the systems.
- Removal of all dirt, dust, lint, etc., caused by cleaning process in areas affected by cleaning process.
- Representative photographs will be taken after cleaning.

ALL
 OK 7/21/05

2. Cleaning, Visual Inspection and Clearance Air Sampling will be performed as follows:

- Cleaning will be performed in accordance with the National Air Duct Cleaners Association Standards (NADCA) ACR 2005. All access will be through existing 6" floor openings.
- Negative air machine shall be attached to the duct system to obtain approximately 2,500 ~~linear~~ cubic feet per minute of air movement across the active duct work space.
- All areas will be air washed using Scand Tech USA High Volume Nozzles or equivalent.
- Air washing will be done using high volume, medium pressure Scand Tech USA Tornado Nozzles, or equivalent (see attached for example equipment). Maximum air pressure at

CUBIC
 OK
 7/21/05



05 0427


- nozzles should not exceed 125 psi with a minimum volume of 80 cubic feet per minute (CFM). Air movement must be of sufficient volume to prevent any cross contamination.
- High volume Tornado Nozzles will be used to move contaminants to the collectors. Use of tube style air whips will not be allowed unless they are capable of dispensing a minimum of 80 CFM of discharge air.
- Air Compressors will be Kaeser ASD 30 or equivalent. Air compressors must generate a minimum of 130 CFM at 125 PSI. Air compressors will use "Y Delta" connections to reduce start up amperage.
- HEPA Air Scrubbers up to 2000 CFM will be used for make up air entering the duct systems.
- Dislodged contaminants will be collected in a HEPA filtration system. All dirt, duct, lint and other accumulations will be removed by approved, HEPA filtered negative air machines (NADCA ACR 2002, 5.3.3) capable of removing a minimum of 4000 CFM of air from the duct system during the cleaning process.
- Following initial air washing, a visual inspection of the cleaned duct area will be performed. As the cleaning work progresses and prior to duct access plate closure, the cleaned duct work area shall be inspected.
- Video inspection equipment will be used to inspect cleaned duct areas (see attached example equipment). The camera lens will be capable of focusing to 1" from surfaces. Inspection equipment will be capable of inspecting ducts of a minimum 1" x 4" dimension up to an approximate distance of 20 meters from one access port.
- All inspected areas will be identified and recorded on VHS format.
- If debris is still observed during the visual inspection, brushing ^{SHALL} be required. If necessary, a variety of brushes and mechanical agitators may be used to dislodge contaminants. If brushing is required, brush cables must be capable of reaching up to 30 meters from one opening. Brushes must be sized specifically for each duct size; Scand Tech USA brushes or equivalent. If brushing is required, whip brushes must be used on all square or rectangular ducts.
- Upon successful completion of the visual inspection, aggressive air sampling within the work area shall be performed as described in Variance Decision File No. 05-0427. Prior commencement of this clearance air sampling, all Walker Duct/Raceway floor opening access ports shall be opened to the work area and leaf blower directed into access port openings.

OR RESIDUE
ex 7/21/05

SHALL ex 7/21/05

If you have any questions please feel free to contact us at (212) 221-7822.

Sincerely,


Amiel Javal
Senior Project Manager

Attachments

cc: Amy Peterson - LMDC
Edward Gerdts - TRC
Vincent Lander - QuES&T



July 7, 2005

File No. 05-0427

Christopher Alonge, P.E.
NYS Department of Labor
Engineering Services Unit
State Campus Bldg. 12, Room 154
Albany, NY 12240

RECEIVED

JUL 08 2005

**MUNICIPAL ENGINEER
ENGINEERING SERVICES UNIT
ALBANY, NY**

**Subject: Additional Information -
Variance Reopening (2) for Walker Duct and Raceway Cleaning Protocols
File No. 05-0427; 130 Liberty Street, New York, NY**

Dear Mr. Alonge,

Per your request, we respectfully submit for consideration this additional information regarding File No. 05-0427 - Variance Reopening (2) for Walker Duct and Raceway Cleaning Protocols dated June 10, 2005. This information supplements the information previously provided.

Additional Information - Isolation and Cleaning of Walker Ducts and Raceways

The Raceways run in an East/West direction. With the exception of Core Building shaft areas, the Raceways run beneath the floor slab and span the entire length of the building (182 feet). The structural column rows are separated by a horizontal distance of approximately twenty-five feet. Typically, there are six (6) rows of Raceways between each row of structural columns.

The Walker Ducts run in a North/South direction. The Walker Ducts are imbedded within the concrete floor slab, interconnect individual Raceways and typically do not span the entire length of the building. The Electrical Plan Drawing (Typical) for the 31st Floor is attached for reference.

A maximum of eight Raceways with their associated Walker Ducts will be cleaned within a single grouping. The actual number of Raceways included within a single grouping will be based on the requirement to maintain a minimum air movement within the duct of 1,000 linear feet per minute. The Raceways and Walker Ducts within a defined grouping will be isolated from the adjacent Raceway by installation of isolation points, within the Walker Ducts, where these systems interconnect.

Cleaning of the Raceways and Walker Ducts will be as follows:

1. Each Raceway and Walker Duct grouping will be cleaned for the entire East to West length by accessing through several existing floor openings.
2. Raceway and Walker Duct cleaning, within each negative pressure work area, will generally proceed from the outside edge of each negative pressure work area (i.e. the North and/or South end of the Building) working back towards the opposite end.
3. The connecting openings in the Walker Ducts, on the perimeter of the defined grouping, will be accessed through the existing floor openings and cleaned using HEPA vacuums.

05-0427

4. Isolation points, to segregate the grouping to be cleaned from the rest of the system, will be installed by using expandable foam in each of the cleaned perimeter Walker Duct openings.
5. Each defined grouping shall be placed under negative pressure by installation of High Volume HEPA Air Scrubbers; as described in the previous submittal. HEPA Filtered Supply air shall be provided at the Supply End of the isolated grouping and a HEPA Filtered Collection Unit shall be installed at the Collection End. This will provide air movement within the isolated grouping of at least 1,000 liner feet per minute.
6. Reverse Air Tornado nozzles, described in the previous submittal, will be inserted through the access opening downstream of the section to be cleaned. Maximum length of air hose to be inserted for cleaning shall be approximately sixty-five (65) feet.
7. The cleaning shall proceed from the Supply End towards the Collection End of the isolated Raceway/Walker Duct grouping. This process will be repeated until cleaning is complete by incrementally moving toward the HEPA negative air collector.

If you have any questions please feel free to contact us at (212) 221-7822.

Sincerely,




Arnel Javal
Senior Project Manager

Attachment

cc: Amy Peterson - LMDC
Edward Gerds - TRC
Vincent Lander - QuES&T

05-0427



06/08/05 16:23 TEL 8605285556

02
05 04 27

June 8, 2005

Vincent M Coluccio, DrPH
TRC
177 Upper Samsonville Road
Olivebridge, New York 12361

RE: 130 Liberty Street, NYC BASIC EQUIPMENT NEEDS for 1 set Approx.\$

The following is a basic equipment list for the specialty requirements. There would be additional small tools and equipment need that most contractors would already have. The only printed Camera price list we have is from 2001. All pricing in our computer is approximately 20% higher. HEPA Equipped Collection units (we do not sell them) very greatly from manufactures. Rental Air Center, Inc. provide the compressors on other Ground Zero projects and are familiar with the requirements.

SCAND TECH LLC

1" Camera, Push Shaft, Reel, Monitor, Charger	\$4,200 to \$5,500
½ Tornado Cleaning Kit 101.012	\$ 800 to \$1,200
¾ inch hose/Chicago fittings \$75. each 50 feet x 4	\$ 300
2 Rotating Cleaning Cables 12 meter & 20 m	\$ 800
Misc. Brushes	\$ 100
	<u>\$6,200 to \$7,900</u>

**VACUUM COLLECTION UNITS Three stage HEPA Equipped
Abatement, Air Care, Meyers Machine, Nikro Industries**


Examples

HEPA AIRE 2500 cfm	\$7,500
HEPA AIRE 4500 cfm	\$9,500

**ELECTRIC AIR COMPRESSORS 100 to 200 cfms 220volt to 480 volt
Rentals Air Center, Inc 908-276-1992**

**AIR SCRUBBERS HEPA EQUIPPED 2000cfm
Rental or New \$2000**

INSPECTION EQUIPMENT



Inspection Camera, 2 inches (49 mm)

Item No.501.001 This small size Inspection Camera is very versatile for vertical as well as horizontal ventilation ducts. The unit is equipped with a high-definition, black-and-white camera module with automatic aperture setting and super wide-angle lens. Focus control can be made from a distance of 0.4" (10 mm). The camera head is activated by a joystick and the movements are directly synchronized. Endless rotation of camera head as well as turning from 0 to 90 degrees. The control unit is equipped with a flat monitor in a solid plastic casing, remote control (joystick) and a cable reel for 65 ft (20 m) cable.

Technical Data: Camera Unit.

Camera: High-definition CCD b/w camera module with automatic aperture setting.
 Super wide-angle lens 0.1" (2.5 mm).
 Photosensitivity: 0.5 lux.

Diameter: Camera head = 2 inches (49 mm).
 Length: Camera head = 5 inches (134 mm).
 Range of rotation: Endless left - right.
 Range of turning: 0 - 90 degrees vertical to horizontal position.
 Weight: 0.6 lb (280 g).
 Illumination: Nine subminiature lamps, 8.4 W total.

Technical Data: Control Unit.

Monitor display: Flat monitor, 3"x2" (81mm x 59 mm).
 Panel: Flip switch, joystick, adjustment for contrast and brightness.
 LCD-Voltage indicator, VCR-connection.
 Cable: Cable reel with special cable, 65 ft (20 m) with metric scale.
 Weight: 10 lbs (4.7 kg).
 Power supply: Battery operated 12V - maintenance-free, long life accumulator.
 Automatic charger. Operation time depending on camera head = 60 - 20 min.
 Case: Black plastic casing with carrier belt.

Accessories: Watertight camera, diameter less than 1 inch (22 mm), with flared head and with 10 ft (3 m), 16 ft (5 m), 33 ft (10 m) or 49 ft (15 m) push-shaft.
 Charging-cable for cigarettelighter outlet in cars, 12 V.



SCAND TECH

MEMBER OF
BSV
 Bureaus of Survey
 Valuations Registrars

MEMBER OF
NADCA
 National Association of
 Duct Cleaning Associations

06/08/05 16:23 TEL 8806285556

05

05 04 27









KUMMERT

Chimney Inspection

↓
Pricelist valide at March 2001

Bernhard Kummert Videoinspektionssysteme - D-97447 Gerolzhofen, Albert-Einstein-Str. 8

+20%
for 2005

Article-No.	Picture	Article	Price
Analog Basic instruments			
4352		Colour Mini Hand Instrument without cable, 12poles, incl. charge station and exchange accu	1.595,00
3588		Mini Hand Instrument without cable, 12poles, incl. charge station and exchange accu	1.095,00
1385		Portable Instrument with fixed cable reel, 20 m cable	1.449,00
1388		Portable Instrument with fixed cable reel, 30 m cable (12poles) and charge device	1.549,00
1776		Multi Inspection Device, with LCD Colour monitor, VHS-video recorder and rotatable cable reel with 20 m cable, 12poles	4.495,00
4283		Colour Portable Instrument with rotatable reel, 20 m cable (12poles) and charge device	2.450,00
1386		Portable Instrument with rotatable reel, 20 m cable (12poles) and charge device	1.895,00
1389		Portable Instrument with rotatable reel, 30 m cable (12poles) and charge device	1.995,00




All Prices are excluded V.A.T., postage and packing. Subject to alteration.

06/08/05 16:23 TEL 8605285556









06

Bernhard Kummert Videoinspektionssysteme - D-97447 Gerolzhofen, Albert-Einstein-Str. 8

+2070 427

Article-No.	Picture	Article	Price
Camera heads			
4015		Colour Glass Cupola Camera, 12poles, swing range 180°, rotating range 360°, diameter 51 mm	1.590,00
3874		SK-22 Black/White Miniature Spring Camera 6poles diameter 22 mm	985,00
3867		CSK-35 Colour Camera, 6poles, waterproof, diameter 35 mm	1.285,00

Attachment camera heads

1522		Reel Connection for art.-no. 1391/4258	185,00
1544		Centring Spring for art.-no. 1391/4258, adjustable - for the variable centering of the Rotating Globe Shape Camera for the inspection from top to bottom inside of the chimney	159,00
1558		Centring Carriage for art.-no. 1391/4258	249,00
4001		Reel Connection for art.-no. 2594/4015	248,00
3839		Spring Guide for art.-no. 2594/4015	71,50
4193		Removable protected cover for art. no. 3874	85,00
4105		Socket clip for Centring Carriage for art. no. 3874 Miniature spring Camera	45,00
4202		Basic connection	197,00

All Prices are excluded V.A.T., postage and packing. Subject to alteration.
All preceding Prices are invalide.




06/08/05 16:23 TEL 8605285556

05 04 27¹







07

Bernhard Kummert Videoinspektionssysteme - D-97447 Gerolzhofen, Albert-Einstein-Str. 8



+2070

Article-No.	Picture	Article	Price
Attachment camera heads			
4262		Centring carriage for system 2000	168,00
4478		Centring Brush Set, 3 Leinstars of Nylon, 200 mm, 300 mm, 400 mm, hole 28 mm	57,00
4184		Connection Spring, 14 cm, 6poles, flexible connection between camera head CSK-35 and GFK rod	187,00

Accessories for pushing camera heads


3923		Camera rod 3m, 6mm, 1*6poles, 1*12poles	270,00
3922		Camera rod 5m, 6mm, 1*6poles, 1*12poles	320,00
4033		Camera rod 10m, 6mm, 1*6poles, 1*12poles	370,00
1571		Camera rod 3m, 6mm, 2*12poles	270,00
1569		Camera rod 5m, 6mm, 2*12poles	320,00
1557		Camera rod 10m, 6mm, 2*12poles	370,00

Camera reel

4337		Mini reel 12poles, zinc-plated, 20 m, rod 4,5 mm	745,00
4336		Large reel zinc-plated, 12poles, 20 m, rod 6 mm	895,00

All Prices are excluded V.A.T., postage and packing. Subject to alteration.
All preceding Prices are invalid

MECHANICAL⁰⁵ 0427 CLEANING



Rotating Cleaning Cable

Item Nos. 228.010 - 238.300

The Rotating Cleaning Cables are connected to a battery - powered drill, up to 33 ft (10 m), or to the Brush Machine, 33 ft (10 m) and up. The inner wire is made from hardened steel and inspected using laser. The outer casing has a diameter of 0.4 inch/10mm.

- * Item Nos. 228.010- 228.100 Cleaning Cable, with 0.11" (2.8 mm) inner wire recommended for duct sizes of 3" - 6" (80 mm - 160 mm) with numerous bends. Available in standard lengths from 3 ft - 30 ft (1m - 10 m). Any preferred length available on special request. Marked with yellow tape at the stop nipple.
- Item Nos. 232.010- 232.120 Cleaning Cable, with 0.13" (3.2 mm) inner wire recommended for duct sizes of 4" - 12" (100 mm - 300 mm) with some bends. Available in standard lengths from 3 ft - 40 ft (1 m - 12 m). Any preferred length available on special request. Marked with blue tape at the stop nipple.
- Item Nos. 238.050- 238.300 Cleaning Cable, with 0.15" (3.8 mm) inner wire recommended for duct sizes of 6" - 24" (160 mm - 600 mm) with few bends. Available in standard lengths from 16 ft - 98 ft (5 m - 30 m). Any preferred length available on special request. Marked with red tape at the stop nipple.
- Item No. 238.200 Cleaning cable with 0.15" (3.8 mm) inner wire and a length of 66 feet (20 m).
- Item No. 228.015 Cleaning cable with 0.11" (2.8 mm) inner wire and a length of 5 feet (1.5 m).
- Item No. 261.160 6" (160 mm) brush for circular ducts - see separate product leaflet.
- Item No. 410.001 Brush Ball - see separate product leaflet.



SCAND TECH

SCANDTECH, USA
 Phone: 1-800-587-3980
 Fax: 1-800-587-3979
 E-Mail Address:
 scanduct@AOL.Com

MEMBER OF
ROVE
ROVING OPERATORS VENDOR ASSOCIATION


MEMBER OF
NADCA
NATIONAL ASSOCIATION OF DUCT CLEANERS

06/08/05 18:23 TEL 8605285556

09

MECHANICAL CLEANING

05 04 27



Soft and hard Nylon Whip Brushes

Item Nos 263.200 - 263.600 Brushes made of hard red/white nylon bristles, and 8" (200 mm) extended soft white nylon bristles. The brushes are designed for use in square and rectangular ducts. The soft white nylon bristles remove dirt from corners. The Brushes are available in sizes from 8"-24" (200 mm-600 mm).

2" & 3" AVAILABLE



SCAND TECH

SCANDTECH, USA

Phone: 1-800-587-1980

Fax: 1-800-587-3979

E-Mail Address:
scanduct@AOL.Com

MEMBER OF
ISOV
International Society of
Vibratory Finishing

MEMBER OF
NADCA
NATIONAL ASSOCIATION OF
DUCT CLEANERS

06/08/05 18:23 TEL 8605285556

COMPRESSED AIR CLEANING 05 0427

10

Rotating Nozzles

100.012	Rotating Brush Nozzle Cleaning Kit, 1/2 inch (12 mm) with an 80 ft (25 m) hose on a reel, shut-off valve and claw coupling. 12 different brushes made of nylon and steel. IMPROVED!	2.695
100.020	Rotating Brush Nozzle Cleaning Kit, 3/4 inch (20 mm) with an 80 ft (25 m) hose on a reel, shut-off valve and claw coupling. 12 different brushes made of nylon and steel. IMPROVED!	3.495
100.025	Rotating Whipstream Nozzle Cleaning Kit, 1 inch (25 mm) with an 80 ft (25 m) hose, shut-off valve and claw coupling. IMPROVED!	2.995

Tornado Nozzles

101.012	* Tornado Nozzle Cleaning Kit, 1/2 inch (12 mm) with a 98 ft (30 m) hose on a reel, shut-off valve and claw coupling. 4 hard plastic jet nozzles with variable spreading angles for different duct sizes. 1 aluminium jet nozzle for ducts made of concrete.	1.195
101.016	Tornado Nozzle Cleaning Kit, 2/3 inch (16 mm) with a 98 ft (30 m) hose on a reel, shut-off valve and claw coupling. 4 hard plastic jet nozzles with variable spreading angles for different duct sizes. 1 aluminium jet nozzle for ducts made of concrete.	1.395
101.025	Tornado Nozzle Cleaning Kit, 1 inch (25 mm) with an 80 ft (25 m) hose, shut-off valve and claw coupling. 1 hard plastic jet nozzle for sheet metal ducts and 1 aluminium jet nozzle for ducts made of concrete.	995

Cleaning Hoses

102.012	Light-weight cleaning hose, 1/2 inch/80 ft (12 mm/25 m).	259
102.112	Cleaning Hose, 1/2 Inch / 98 ft (12 mm / 30 m).	289
102.116	Cleaning Hose, 2/3 Inch / 98 ft (16 mm / 30 m).	510
102.120	Cleaning Hose, 3/4 inch / 80 ft (20 mm / 25 m).	917
102.125	Cleaning Hose, 1 inch / 82 ft (25 mm / 25 m).	487

Feeding Hoses

103.010	Feeding Hose 0.4 inch/98 ft (10 mm/30 m) with claw coupling and quick coupling.	160
103.020	Feeding hose (Mantex) 1 inch/65 ft (25 mm/20 m) with 2 claw couplings.	255
103.060	Feeding hose (Mantex) 1 inch/197 ft (25 mm/60 m) with 2 claw couplings.	708

*** DELETE REEL ! EXTRA TETS - 400.00**

Scand Tech, USA, L.L.C.

P. O. Box 265 440 John Fitch Blvd South Windsor, CT 06074 USA
 Phone 800-587-3980 Fax 800-587-3979 E-Mail: scanduct@aol.com

06/08/05 16:23 TEL 8605285558

11

MECHANICAL CLEANING 05 04271

Powerful Brush Machines

210.670	Brush Machine, 110 V, Single-phase, 740 rpm.	2 695
220.670	Brush Machine, 220 V, Single-phase, 740 rpm.	2 695

Soft and flexible cleaning cable, 0.11 inch (2.8 mm) for duct sizes from 3"-6" (80 - 160 mm).

228.010	Cleaning Cable, 3ft (1 m).	103
228.015	Cleaning Cable, 5ft (1.5 m).	139
228.030	Cleaning Cable, 10 ft (3 m).	160
228.050	Cleaning Cable, 16 ft (5 m).	187
228.070	Cleaning Cable, 23 ft (7 m).	229
228.100	Cleaning Cable, 33 ft (10 m).	296

Medium and flexible cleaning cable, 0.13 inch (3.2 mm) for duct sizes from 4"-12" (100 - 300 mm).

232.010	Cleaning Cable, 3 ft (1 m).	103
232.015	Cleaning Cable, 5 ft (1.5 m).	139
232.030	Cleaning Cable, 10 ft (3 m).	160
232.050	Cleaning Cable, 16 ft (5 m).	187
232.070	Cleaning Cable, 23 ft (7 m).	229
232.100	Cleaning Cable, 33 ft (10 m).	296
232.120	Cleaning Cable, 39 ft (12 m).	339

Hard and flexible cleaning cable, 0.15 inch (3.8 mm) for duct sizes from 6"-24" (160 - 600 mm).

238.050	Cleaning Cable, 16 ft (5 m).	187
238.070	Cleaning Cable, 23 ft (7 m).	229
238.100	Cleaning Cable, 33 ft (10 m).	296
238.120	Cleaning Cable, 39 ft (12 m).	339
238.150	Cleaning Cable, 49 ft (15 m).	405
238.200	Cleaning Cable, 66 ft (20 m).	458
238.250	Cleaning Cable, 82 ft (25 m).	544
238.300	Cleaning Cable, 98 ft (30 m).	608

Hard and flexible cleaning cable with Jetstream-function. Suitable for rectangular ducts 10"-28" (250 mm-700 mm)

250.150	Rotating JetStreamCable, 49 ft (15 m).	799
250.200	Rotating JetStreamCable, 65 ft (20 m).	899
250.250	Rotating JetStreamCable, 82 ft (25 m).	999
250.300	Rotating JetStreamCable, 98 ft (30 m).	1 099

Brushes for normal pollution in circular ducts

261.100	Nylon Brush, 4 inches (100 mm).	18
261.125	Nylon Brush, 5 inches (125 mm).	20
261.160	Nylon Brush, 6 inches (160 mm).	22
261.200	Nylon Brush, 8 inches (200 mm).	24
261.250	Nylon Brush, 10 inches (250 mm).	26
261.315	Nylon Brush, 12 inches (315 mm).	29
261.400	Nylon Brush, 16 inches (400 mm).	34
261.500	Nylon Brush, 20 inches (500 mm).	48
261.600	Nylon Brush, 24 inches (600 mm).	54
261.700	Nylon Brush, 28 inches (700 mm).	61
261.800	Nylon Brush, 32 inches (800 mm).	65

Scand Tech, USA, L.L.C.

P. O. Box 265 440 John Fitch Blvd South Windsor, CT 06074 USA
 Phone 800-587-3980 Fax 800-587-3979 E-Mail: scanduct@aol.com

06/08/05 16:23 TEL 8605285556

12
Price USD


Item no.	Description	Price USD
Brushes for severe pollution in circular ducts		
262.100	Nylon Brush reinforced with steel, 4 inches (100 mm).	18
262.125	Nylon Brush reinforced with steel, 5 inches (125 mm).	20
262.160	Nylon Brush reinforced with steel, 6 inches (160 mm).	22
262.200	Nylon Brush reinforced with steel, 8 inches (200 mm).	24
262.250	Nylon Brush reinforced with steel, 10 inches (250 mm).	27
262.315	Nylon Brush reinforced with steel, 12 inches (315 mm).	29
262.400	Nylon Brush reinforced with steel, 16 inches (400 mm).	34
262.500	Nylon Brush reinforced with steel, 20 inches (500 mm).	48
262.600	Nylon Brush reinforced with steel, 24 inches (600 mm).	54
262.700	Nylon Brush reinforced with steel, 28 inches (700 mm).	61
262.800	Nylon Brush reinforced with steel, 32 inches (800 mm).	65
Brushes for normal pollution in rectangular ducts (Whip Brushes)		
→ 263.015		25
263.200	Soft and hard Nylon Whip Brush, 8 inches + 8 inches (200 mm + 200 mm).	27
263.300	Soft and hard Nylon Whip Brush, 12 inches + 8 inches (300 mm + 200 mm).	31
263.400	Soft and hard Nylon Whip Brush, 16 inches + 8 inches (400 mm + 200 mm).	37
263.500	Soft and hard Nylon Whip Brush, 20 inches + 8 inches (500 mm + 200 mm).	52
263.600	Soft and hard Nylon Whip Brush, 24 inches + 8 inches (600 mm + 200 mm).	60
Brushes for internally insulated ducts		
→ 264.085		16
264.100	Soft Polythene Brush, 3 inches (85 mm).	18
264.125	Soft Polythene Brush, 4 inches (100 mm).	20
264.160	Soft Polythene Brush, 5 inches (125 mm).	22
264.200	Soft Polythene Brush, 6 inches (160 mm).	27
264.250	Soft Polythene Brush, 8 inches (200 mm).	29
264.315	Soft Polythene Brush, 10 inches (250 mm).	31
264.400	Soft Polythene Brush, 12 inches (315 mm).	34
264.500	Soft Polythene Brush, 16 inches (400 mm).	48
264.630	Soft Polythene Brush, 25 inches (630 mm).	54
Brushes for severely polluted ducts, for example kitchen ducts		
265.085	Steel brush, 3 inches (85 mm).	16
265.110	Steel brush, 4 inches (110 mm).	18
265.140	Steel brush, 6 inches (140 mm).	20
265.170	Steel brush, 7 inches (170 mm).	22
265.230	Steel brush, 9 inches (230 mm).	27
265.290	Steel brush, 11 inches (290 mm).	29
265.350	Steel brush, 14 inches (350 mm).	31
265.425	Steel brush, 17 inches (425 mm).	34
265.525	Steel brush, 21 inches (525 mm).	48
265.625	Steel brush, 25 inches (625 mm).	54
Spare Parts		
240.028	Inner thread, 0.11 inch (2.8 mm), per ft.	2
240.032	Inner thread, 0.13 inch (3.2 mm), per ft.	2
240.038	Inner thread, 0.15 inch (3.8 mm), per ft.	2
242.028	Brush nipple, 0.11 inch (2.8 mm).	31
242.032	Brush nipple, 0.13 inch (3.2 mm).	31
242.038	Brush nipple, 0.15 inch (3.8 mm).	31
243.028	Stop nipple, 0.11 inch (2.8 mm).	31
243.032	Stop nipple, 0.13 inch (3.2 mm).	31
243.038	Stop nipple, 0.15 inch (3.8 mm).	31

Scand Tech, USA, L.L.C.

P. O. Box 265 440 John Fitch Blvd South Windsor, CT 06074 USA
 Phone 800-587-3980 Fax 800-587-3979 E-Mail: sconduct@aol.com

COMPRESSED AIR CLEANING

05 04 21



Item No. 101.012 Tornado Nozzle Cleaning Kit, 1/2 Inch (12 mm) with a 98 ft (30 m) hose on a reel, shut-off valve and claw coupling. 4 hard plastic jet nozzles with variable spreading angles for different duct sizes. 1 aluminium jet nozzle for ducts made of concrete. Recommended for: Duct sizes from 3" - 12" (80 mm-300 mm). Recommended compressor capacity: 185 cfm (5.2 m3 / min) at 116 psi (8 bar).

Item No. 101.016 Tornado Nozzle Cleaning Kit, 3/4 Inch (19 mm) with a 98 ft (30 m) hose on a reel, shut-off valve and claw coupling. 4 hard plastic jet nozzles with variable spreading angles for different duct sizes. 1 aluminium jet nozzle for ducts made of concrete. Recommended for: Duct sizes from 6" - 24" (160 mm-600 mm). Recommended compressor capacity: 185 cfm (5.2 m3 / min) at 116 psi (8 bar).

Item No. 101.025 Tornado Nozzle Cleaning Kit, 1 Inch (25 mm) with an 80 ft (25 m) hose, shut-off valve and claw coupling. 1 hard plastic jet nozzle for sheet metal ducts and 1 aluminium jet nozzle for ducts made of concrete. Recommended for: Duct sizes from 12" - 47" (300 mm-1200 mm). Recommended compressor capacity: 185 cfm (5.2 m3 / min) at 116 psi (8 bar).

Item No. 103.010 Feeding Hose 0.4" / 98 ft (10mm/30m) with claw coupling/ quick coupling. To be used together with Jetstream Cables, Air and Blaster Guns or other Air Tools.

Item No. 103.020 Feeding Hose black (Mantex) 1" / 65 ft (25mm/20m) with two claw couplings.

Item No. 130.001 Connection central for two Compressed Air Cleaning Kits. This Y-type connection central connects with a claw coupling to an 1 inch (25 mm) feeding hose from the compressor. Allowing you to connect two different Compressed Air Cleaning Kit with claw couplings.

Item No. 140.805 Air Gun recommended to be used in smaller ducts -from 3 inch to 5 inch (80 mm-125 mm). The kit consist of a 0.3 inch / 33 ft (8 mm - 10 m) stiff plastic hose and two plastic jet nozzles for forward or reverse directed compressed air. Recommended compressor capacity: 10 cfm (250 l / min) at 87 psi (6 bar).

Item No. 150.003 Shut-off valve 1 inch (25mm) with two claw couplings.



SCAND TECH

SCANDTECH. USA

Phone: 1-800-587-3980

Fax: 1-800-587-3979

E-Mail Address:

scanduct@AOL.Com

MEMBER OF
DOVR
Duct and Ventilation Services
Ventilation Services

MEMBER OF
NADCA
National Air Duct Cleaning Association

05-0427

RECEIVED

JUN 29 2005

**PROPOSED PILOT PROGRAM
WORK PLAN****PRINCIPAL ENGINEER
ENVIRONMENTAL SERVICES UNIT
ALBANY, NY****FOR THE
REMOVAL OF ALUMINUM COLUMN COVERS AND FASCIA WITH
NON-FRIABLE ACM CAULKING MATERIAL****At****130 Liberty Street
New York, New York****Lower Manhattan Development Corporation
1 Liberty Plaza
New York, New York 10006****Prepared by:
TRC Environmental Corporation
1430 Broadway
New York, New York 10018****June 24, 2005**

05-0427

- I. **DESCRIPTION OF WORK:** The building located at 130 Liberty Street, New York, New York is scheduled for cleaning and deconstruction. Non-friable asbestos caulking material exists in the factory installed joints inside the aluminum column covers and fascia. The non-friable ACM caulking is a Category II non-friable material as defined by NESHAPS, 40 CFR Part 61 Subpart (M).

Aluminum column covers span the height of the building at each column, and fascia are present around the building façade at the ground, mechanical and roof levels. In addition, aluminum covers and fascia are located inside the building within the lobby level. See photo below.



Figure 1

05-0427



Figure 1

The United States Environmental Protection Agency (USEPA), the New York State Department of Labor (NYS DOL), and the New York City Department of Environmental Protection (NYCDEP) agreed to review a pilot project submitted by the Lower Manhattan Development Corporation (LMDC) to assess the concentrations of asbestos in air, if any, generated during the proposed aluminum column cover and fascia removal operations. The results from the pilot project are intended to assist the USEPA, NYSDOL, and NYCDEP in determining whether or not to continue to require tent enclosures during removal of aluminum covers and associated exterior non-friable caulking material as part of the deconstruction. The work under this pilot project will be performed within tent enclosures with a remote decontamination unit.

To ensure that the pilot project is performed on aluminum covers with non-friable asbestos-containing caulking, three (3) representative bulk caulking samples shall be collected and analyzed for asbestos at each of the four (4) pilot project locations. The Pilot Project will be performed at four (4) locations where the presence of ACM caulk has been verified.

Prior to initiating the Pilot Project at any of the selected locations, the contractor will remove porous materials from within the enclosure and thoroughly clean all exposed non-porous surfaces at that Pilot Project location. Removal of porous materials within the aluminum column enclosure shall be conducted within an exterior negative pressure tent enclosure per NYSDOL Approved Variance Decision Amendment entitled "Amendment: Revised Procedures & Conditions" under file # 05-

05-0427

0427 (~~05-0427~~ attached). This will ensure that the conditions existing within the column cover enclosure, during the Pilot Project, are representative of the actual field conditions anticipated during removal of the aluminum covers during deconstruction of the building.

The Pilot Project will be conducted within the same negative pressure tent upon achieving satisfactory clearance air sampling results using the procedures described herein. The Pilot Project work shall be performed by a NYSDOL Licensed Asbestos Abatement Contractor with appropriately certified asbestos handlers. The existing basement remote decontamination unit shall be utilized for work associated with this Pilot Project.

Pilot Project work includes cutting of aluminum column covers into manageable sections and packaging them for disposal. Asbestos caulking material shall remain intact but will be cut as necessary to represent anticipated site conditions. Pilot project work will be completed using the same tent enclosure as pre-pilot project work.

II. WORK PLAN GENERAL NOTES:

1. A detailed layout of the four (4) pilot project locations, columns and enclosures, and tent structure are presented in the attached plans.
2. Certified individuals and contractors shall perform the work in compliance with the requirements of all applicable laws, rules, and regulations including site-specific variance decisions and conditions.
3. The Abatement Contractor shall file and pay all required notifications and permit fees to complete the pilot project.
4. The Abatement Contractor shall complete at least four (4) different work areas under this pilot project. The exact locations of the work areas are identified in the attached plans.

III. TECHNICAL REQUIREMENTS: The Contractor shall use work methods and equipment during the pilot project that represent abatement procedures anticipated to be employed for the remainder of the building during Deconstruction Activities.

Pilot Project Work: Includes the cutting of aluminum column covers into manageable sections with the asbestos caulking material intact to the extent feasible. Pilot project work will be completed using the same tent enclosure as pre-pilot project work.

1. Using the same tent enclosure during the pre-pilot project work, the abatement contractor shall install an additional layer of clean six-mil fire retardant polyethylene sheeting inside each tent enclosure.

05-0427

2. The aluminum column covers with asbestos caulking shall be cut into manageable pieces and removed from the structure, using non-abrasive mechanical method (i.e. power shear equipment). Cutting of asbestos caulking shall be limited to the extent possible. Asbestos caulking shall be wetted prior to being cut and during cutting at the point of removal. Cut aluminum panels shall be double-wrapped with six-mil fire-retardant polyethylene sheeting or bagged and properly labeled for disposal as asbestos waste.

NEGATIVE AIR SYSTEM

3. Engineering controls shall not be applied to each tent and therefore no air volume changes shall occur within each tent during the non-friable caulking on aluminum cover removal.

cm
7/21/05

4. Inside and outside of each tent, continuous air monitoring shall be performed during all operations. Three (3) TEM air samples inside and three (3) TEM air samples outside the tent enclosure shall be collected.
5. A third party air monitoring entity shall perform the air sampling described above.
6. The air sampling analyses from each of the four (4) tents shall be assessed and shall be deemed acceptable only if all analyses are less than 70 s/mm² or less than the ambient concentration, which ever is greater.
7. Any tent inside which any individual air sample analysis exceeds 70 s/mm² shall be subjected to final cleaning and final air clearance procedures for asbestos, pursuant to file # 05-0427, before dismantling.
8. Where the in-tent air monitoring gives all acceptable results as per item 6 above, removal of the remaining vertical aluminum column covers may be permitted to occur using continuous spraying of amended water at all points of cutting, use of polyethylene drop cloth under each work area and HEPA vacuuming of polyethylene drop cloth, without tent enclosures.
9. The results of the Pilot Program shall be transmitted to the USEPA, NYSDOL and NYCDEP for their review and determination as to whether or not tent enclosures will be required during deconstruction.


UPON REGULATORY AGENCY APPROVAL

cm
7/21/05

05-0427

General Notes:


1. The work under this pilot project will include the construction of four modified tent enclosures with a remote worker and waste decontamination units.
2. The pilot project will be completed subsequent to the removal of contaminated fire proofing material applied on the structural beams and clean up of overpray material inside each aluminum column cover enclosure using Exterior Negative Pressure Tent Enclosure per NYSDDL Variance Decision Amendment File No. 05-0427. Pilot project will include the cutting of aluminum column cover into manageable sections with the asbestos caulking material intact. Project will be completed using the same tent enclosure used for the previous fireproofing work.
3. A remote decontamination unit shall be established before the commencement of any work under this pilot project.
4. All work under this pilot project shall be performed by a Certified Asbestos Abatement Contractor.





 LMDC Liberty Maintenance & Construction Corporation 130 LIBERTY STREET	1st FLOOR Abatement Plan Pilot Project	DATE	A-1
		SCALE	
 TRC THE ENVIRONMENTAL CORPORATION 1000 ROUTE 92 SUITE 200 FORT MONMOUTH, NJ 08040 PHONE: 732.271.1827 FAX: 732.271.1840	PROJECT NO. 05-0427 SHEET NO. 26 OF 26		




05-0427

 LMDC <small>LIBERTY MUNICIPAL DEVELOPMENT CORPORATION</small>	130 LIBERTY STREET										
	1st FLOOR Abatement Plan Pilot Project										
<table border="1"> <tr> <td>Project No.</td> <td>05-0427</td> </tr> <tr> <td>Phase</td> <td>PRELIMINARY</td> </tr> <tr> <td>Date</td> <td>06/17/05</td> </tr> <tr> <td>Scale</td> <td>AS SHOWN</td> </tr> <tr> <td>Sheet No.</td> <td>D-1</td> </tr> </table>	Project No.	05-0427	Phase	PRELIMINARY	Date	06/17/05	Scale	AS SHOWN	Sheet No.	D-1	
Project No.	05-0427										
Phase	PRELIMINARY										
Date	06/17/05										
Scale	AS SHOWN										
Sheet No.	D-1										

 TRC <small>TRC ENGINEERING & CONSTRUCTION</small>	130 LIBERTY STREET										
	1st FLOOR Abatement Plan Pilot Project										
<table border="1"> <tr> <td>Project No.</td> <td>05-0427</td> </tr> <tr> <td>Phase</td> <td>PRELIMINARY</td> </tr> <tr> <td>Date</td> <td>06/17/05</td> </tr> <tr> <td>Scale</td> <td>AS SHOWN</td> </tr> <tr> <td>Sheet No.</td> <td>D-1</td> </tr> </table>	Project No.	05-0427	Phase	PRELIMINARY	Date	06/17/05	Scale	AS SHOWN	Sheet No.	D-1	
Project No.	05-0427										
Phase	PRELIMINARY										
Date	06/17/05										
Scale	AS SHOWN										
Sheet No.	D-1										



Detail 1: Actual Photo of Column F-1 & G-1




Area 1&2: Columns F-1 & G-1 Work Area Layout (See Detail 1)



05-0427



Detail 2: Actual Photo Of Column H-2 & H-5



Area 3&4: Columns H-2 & H-5 Work Area Layout (See Detail 2)

 130 LIBERTY STREET	1st FLOOR Abatement Plan Pilot Project		D-2
	 TRC ENVIRONMENTAL CORPORATION 110 BROADWAY 10TH FLOOR NEW YORK, NY 10038 PHONE: 212 512-1100 FACSIMILE: 212 512-1100	DATE: _____ DRAWN BY: _____ CHECKED BY: _____ APPROVED BY: _____	